

Portable Compressors

M500-2



Ready where it's needed, when it's needed

The M500-2 is an ultra-reliable source of oil-free compressed air. It is a perfect fit for petro-chemical, plastics, food processing, pharmaceutical, electronics, pipeline, and other industrial plants needing oil-free air during maintenance /repair shutdowns or to provide auxiliary air during peak production periods.

Powered by the dependable 600 hp Caterpillar C18 diesel engine, the M500-2 is engineered for fuel efficiency and ease of operation. With a full load fuel consumption of 21 gal/hr and a 248 gallon fuel tank, M500-2 delivers up to 1600 cfm continuously for up to 12 hours. Run time

can be extended using the external fuel connection (standard).

The SIGMA CONTROL® Mobil 2 matches air flow to meet varying air demand while maintaining steady pressure. With standard Proemion telematics, KAESER fleet management is at your fingertips. Operating status and maintenance reminders are all available via laptop, smartphone, or tablet to avoid unscheduled downtime. M500-2 can be started remotely and the geofencing feature can prevent unauthorized use.

Features:

- Pressures from 58 to 150 psig
- Caterpillar C18 diesel engine
- Stage IV, Tier 4 Final exhaust emissions
- SIGMA CONTROL® Mobil 2
- Proemion telematics with GPS/GSM-modem for MOBILAIR® fleet management
- Up to 12 hours operation on one tank of fuel
- Switchable fuel supply
- Aftercooler with moisture separator
- Adjustable discharge temperature

Technical Specifications

Model	COMPRESSOR					Make	DIESEL ENGINE			Fuel Tank Capacity (gal)	PACKAGE			DIMENSIONS L* x W x H (in.)
	Free Air Delivery						Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)		AdBlue Capacity (gal)	Weight (lb.)	Outlets	
	100 psig (cfm)	125 psig (cfm)	135 psig (cfm)	140 psig (cfm)	150 psig (cfm)									
M500-2	1600	1550	1530	1500	1340	Caterpillar C 18	600	1900	1250	248	12	26,235	1 x 3" Flg 1 x 1" NPT	237 x 90 x 110

*Length without tow bar

Sound level maximum is 76 db(A) at 23 feet

Specifications are subject to change without notice.

Standard Features M 500-2

Controls

- Status and maintenance condition monitoring
- Selectable pressure from: 58 to 150 psig
- Adjustable air discharge temperature up to 149°F
- GPS/GSM-modem
- Remote start via radio remote controller
- Switchable from partial load to dual control
- Automatic start-stop mode

Maintenance

- MOBILAIR® fleet management
- Central fluid draining ports
- LED-illuminated machine interior

- Exhaust treatment: DPF/SCR +
- Connection to external AdBlue tank
- Additional 10.5 gallon engine oil reserve
- Roof top service access

Operation

- Compressed air aftercooler (18°F Δ T nominal)
- Centrifugal moisture separator
- Switchable to external fuel supply for extended operation
- 120V battery charger
- Heaters for engine cooling agent, compressor gear oil, hydraulic oil (120V external)
- Heater for condensate drain and fuel filter (24V on-board)

Transport and Safety

- Pivoting front axle and tow bar
- Lifting eyes (double-strap lifting)
- Fork lift pockets
- Parking brake
- Spark arrestor and engine shut off valve
- Closed floor pan for complete fluid containment

Warranty

- Standard two year warranty
- Optional five year airend warranty



Built for a lifetime.



www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Vérendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda.
3a calle 6-51, zona 13
Colonia Pamplona
01013-Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com

